

DIAPHRAGM PUMPS

The 2" Diaphragm Pumps are used throughout the industry with great effect for all type of fluid transfers; they are small and portable and with minimum moving parts are easily maintained.

- Air driven, can be safely operated in hazardous areas
- Positive displacement
- Self priming
- Durable and reliable

The diaphragm pump is suitable for various applications, capable of pumping a wide range of viscosities, solids and shear sensitive products.

- Maximum flow rate 675 litres / per min (178 gpm)
- Maximum discharge pressure 125 psi (8.6 bar)
- Maximum size solids 6.4mm (1/4")
- Maximum air consumption 100 Cu.Ft. per min
- Displacement per stroke 3.1 litres (0.81 gallons)
- 2" Inlet
- 2" Outlet

SPECIFICATION

Weight and Dimensions:

(L) 36cm x (W) 42cm x (H) 74cm

Unit Weight: 32kg

Air Consumption:

Requires a supply of air between 10 to 125 psi (0.7 to 8.6 bar)



RENTAL & PURCHASE

The 2" Diaphragm Pump is available for rental (short term or long term) or purchase and is supplied complete with:

- 25ft of 2" Suction Hose and Fittings
- 25ft of 2" Discharge Hose and Fittings
- 50ft of 1" Anti Static Air Supply Hose and Fittings
- Copy of Operating Manual

CONTACT

For further information on the Diaphragm Pumps, please contact us:

ITS Environmental Services Ltd
Woodside, Sauchen
Inverurie, Aberdeenshire AB51 7LP

t 01330 830240 f 01330 830249 e sales@its-uk.co.uk
www.its-uk.co.uk